

## FIRE SPRINKLER PROTECTION SYSTEM INSPECTION FOR RESPONSIBLE MAINTENANCE EMPLOYEES

Property Name:	In:	spector:		
Property Address:	Date:			
This Report Covers:   Monthly	☐ Quarterly	☐ Annual	☐ Five-Year	
Monthly Inspection				
☐ Yes ☐ No ☐ N/A	Gauges – normal water p	Gauges – normal water pressure maintained		
	Control Valves			
☐ Yes ☐ No ☐ N/A	In the correct, (open or closed) position			
☐ Yes ☐ No ☐ N/A	Sealed, locked, or supervised			
☐ Yes ☐ No ☐ N/A	Accessible			
☐ Yes ☐ No ☐ N/A	Free from damage or leaks			
☐ Yes ☐ No ☐ N/A	Proper Signage			
	Alarm Valves			
☐ Yes ☐ No ☐ N/A	Free from damage			
☐ Yes ☐ No ☐ N/A	Accessible			
☐ Yes ☐ No ☐ N/A	Retard chambers/alarm	drains not leaking		
Quarterly Inspection				
☐ Yes ☐ No ☐ N/A	Alarm Devices – free from damage			
☐ Yes ☐ No ☐ N/A	Hydraulic data nameplate – securely attached to riser/legible			
	Fire Department Con	nections		
☐ Yes ☐ No ☐ N/A	Visible and accessible			
☐ Yes ☐ No ☐ N/A	Coupling/swivels operate correctly			
☐ Yes ☐ No ☐ N/A	Plugs/caps are in place			
☐ Yes ☐ No ☐ N/A	Gaskets are not damaged			
☐ Yes ☐ No ☐ N/A	Identification signs are in place			
☐ Yes ☐ No ☐ N/A	Ball drip valve is function	nal		
	Pressure Reducing V	'alve		
☐ Yes ☐ No ☐ N/A	In the open position/not leaking			
☐ Yes ☐ No ☐ N/A	Maintaining downstream pressure			
☐ Yes ☐ No ☐ N/A	In good condition			

Annual Inspection		
	Sprinklers (visible)	
☐ Yes ☐ No ☐ N/A	No damage or leaks	
☐ Yes ☐ No ☐ N/A	Free of corrosion, foreign material, or paint	
☐ Yes ☐ No ☐ N/A	Installed in proper orientation	
☐ Yes ☐ No ☐ N/A	Fluid in glass bulbs	
☐ Yes ☐ No ☐ N/A	Spare sprinklers – proper number and type. Complete with wrench?	
☐ Yes ☐ No ☐ N/A	Hangers and seismic bracing – not damaged or loose	
	Pipes and Fittings (visible)	
☐ Yes ☐ No ☐ N/A	In good condition/no external corrosion	
☐ Yes ☐ No ☐ N/A	No leaks or mechanical damage	
☐ Yes ☐ No ☐ N/A	Correct alignment-no external loads	
☐ Yes ☐ No ☐ N/A	Hose racks – inspected per NFPA 1962	
☐ Yes ☐ No ☐ N/A	Building – wet piping not exposed to freezing temperatures	
Five-Year Inspection		
☐ Yes ☐ No ☐ N/A	Alarm valve interior including strainers, filters, and restriction orifice	
☐ Yes ☐ No ☐ N/A	Check valve-internal moves freely, in good condition	
☐ Yes ☐ No ☐ N/A	Obstruction inspection-no foreign or obstructing material found	
Comments		
Signature:	Date:	
License/Certification No :		

Annual inspections, repairs and/or modifications must be performed by a licensed Idaho Fire Sprinkler Contractor pursuant to Idaho Statute 41-254(7) & IDAPA 18.08.02.